



SMALL, BUT MIGHTY

THE ON-CAMERA HERO
FOR HYBRID SHOOTERS



"AN ABSOLUTE GAME CHANGER,
NEO 3 PRO IS BY FAR THE BEST LED
LIGHT PANEL WE'VE EVER USED"



DIGITAL CAMERA WORLD



HIGH SPEED
RGBWW FLASH



16.7M COLOURS
(RGBWW)



2500 DIGITAL
FILTERS



TOUCHSCREEN
DISPLAY



NATIVE IOS &
ANDRIOD APP



[ROTOLIGHT.COM/NEO3PRO](https://rotolight.com/neo3pro)



IMAGEMAKER KIT

RL-NEO3-PRO

BATTERY | POUCH | DOME | BALLHEAD



STUDIO KIT

RL-NEO3PRO-KIT

BATTERIES | HARDCASE | DOMES | BALLHEADS | STANDS



PORTAIT KIT

RL-PORTRAIT-P

AEOS 2 PRO | NEO 3 PRO | BATTERIES | BAG | YOKE

AVAILABLE BUNDLES

“THE ROTOLIGHT NEO 3 PRO IS THE BEST LIGHT AVAILABLE FOR YOUR MONEY”

MAT GALLAGHER - T3



“ONE OF THE BEST MONEY CAN BUY. ANY SERIOUS SHOOTER ABSOLUTELY NEEDS TO ADD THIS TO THEIR ARSENAL”

DIGITAL CAMERA WORLD



“GREAT POWER OUTPUT FOR THE MONEY, SIMPLE TO USE, AND MASSIVE RANGE OF COLOUR.”

DP REVIEW



TECHNICAL SPECIFICATIONS

Small but mighty, NEO 3 PRO is the brightest LED on-camera light ever made. Experience unrivalled power and industry-first innovations in a compact form factor you can take anywhere. NEO 3 PRO combines the shoot what you see benefits of continuous light, with a High Speed Sync RGBWW flash for unlimited creative possibilities.

TECH SPECS	
Peak Output (Lux) @ 3ft	6802 (continuous) 10,700 (flash)
Lux at 3ft F-stop at ISO 100/200/400	6802 F10/ F14/ F20
Lux at 6ft F-stop at ISO 100/200/400	1700 F4/ F5.6/ F7.1
Lux at 9ft F-stop at ISO 100/200/400	756 F2.8/ F3.5/ F5
TLCI	99
CRI	95
Power Consumption	60W
Battery Type	NPF-750, 7.4V, 50W
Mounting	1/4" - 20 or Cold shoe
Dimensions	145mm(W) x 50mm(D)
Wireless Control	WIFI & Bluetooth via IOS & Android app
Beam Angle	50 degrees
Max Shutter Speed Sync	1/8000th
Min Flash Duration	1/2500

	NEO 3 PRO	Rotolight NEO 3	Litepanels Lykos+	Rosco DMG Dash	Luxli Cello 10	Aputure MC RGBWW
High Speed Sync Flash	✓	✓	✗	✗	✗	✗
Touchscreen Interface	✓	✓	✗	✗	✗	✗
Full Colour Display	✓	✓	✗	✗	✓	✗
Digital Filters	2500	2500	✗	137	150	✗
Special Effects	16	12	✗	5	✗	9
Weight	354g	354g	500g	367g	374g	130g
Kelvin Range	3000-10000 Kelvin	3000-10000 Kelvin	3200-5600 Kelvin	1700-10000 Kelvin	3000-10000 Kelvin	3200-6500 Kelvin
FDIM	✓	✗	✗	✗	✗	✗
Master of Light Presets	100+	✗	✗	✗	✗	✗
Wireless Trigger Compatibility	Godox, Profoto, Elinchrom, Pixapro, Neweer	Elinchrom Skyport	✗	✗	✗	✗
Peak Brightness (1m) (lux)	5509	4541	2148	320	1239	100

*Lux measured at 4600K using Sekonic c7000 using firmware 3.01 readings may vary depending on light meter used and testing environment.

All third-party photometrics taken from latest product information sheets and bhphoto.com, accessed in November 2022. Rotolight, NEO, Litepanels, Luxli, are registered trademarks and the exclusive property of their respective owners. No association is intended or implied. Pricing based on full retail prices in USD at BHphoto.com as of November 2022.