

MODEL		CH-S09FTXAM-SC	CH-S12FTXAM-SC	CH-S18FTXAM-SC	CH-S24FTXAM-SC	
Kapaciteta	Hlajenje	kW	0,80/2,70/3,80	0,90/3,51/4,40	0,85/5,30/6,30	1,80/7,10/7,80
	Ogrevanje		0,90/3,00/4,25	0,90/3,81/4,70	1,05/5,35/7,00	1,50/7,30/9,40
Priključna moč	Hlajenje	kW	0,10/0,67/1,30	0,22/0,99/1,40	0,10/1,58/2,30	0,45/2,03/2,90
	Ogrevanje		0,15/0,68/1,40	0,22/0,98/1,65	0,24/1,39/2,35	0,35/1,87/3,50
SEER		-	8,50	7,20	7,30	7,00
SCOP		-	4,60	4,10	4,20	4,30
En. razred	Hlajenje	-	A+++	A++	A++	A++
	Ogrevanje		A++	A+	A+	A+

NOTRANJA ENOTA

Pretok zraka	m³/h	610/570/540/470 /440/420/390	680/620/560/490 /450/420/390	1000/850/760/650 /580/520/450	1000/850/760/580 /520/450/400
Zvočna moč	dB(A)	38/37/34/31/26/23/22	41/38/36/33/30/27/25	45/42/40/37/34/29/26	48/44/41/40/38/36/33
Nastavljiva temperatura	°C	16~30	16~30	16~30	16~30
Dimenzije	mm	837×293×200	837×293×200	993×311×222	993×311×222
Brez žični upravljalac	-	YBEIF (IR)	YBEIF (IR)	YBEIF (IR)	YBEIF (IR)
Opcijski žični upravljalac	-	XK76	XK76	XK76	XK76

ZUNANJA ENOTA

Območje delovanja		°C	-15~50	-15~50	-15~50	-15~50
			-25~30	-25~30	-25~30	-25~30
Grelec kompresorja / zbiralnika kondenza	-	-	Da / Da	Da / Da	Da / Da	Da / Da
Zvočna moč	dB(A)		50	52	56	59
Hladilno sredstvo	Tip	-	R32	R32	R32	R32
	Količina	kg	0,53	0,57	0,85	1,40
Dolžina instalacije	Celotna	m	15	15	25	25
	Višina		10	10	10	10
Dimenzije	mm		732×555×330	732×555×330	802×555×350	958×660×402