



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® BRIMIC S3S ESD

SAFETY SHOES



DRY AIR



REFLECTIVE



WATER  
REPELLENT



DEFUSE  
CONTROL



NONMETALLIC



ESD

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® BRIMIC S3S

SAFETY SHOES

**ARTICLE** G3412

**MATERIAL**

Upper MICROFIBER synthetic fibre, 1,4 mm / TPU  
 Lining MESH-type laminated breathable fabric  
 Outsole PU/PU, two-component coating, oil resistant, antistatic, anti-slip  
 Toe cap Fiberglass  
 Plate Kevlar  
 Insole EVA with shock absorbing construction

**SIZE** 35-48

**UNIT** pair

**PACKAGE**

Units in a carton 10 pairs  
 Units in a box 1 pair

**DIMENSIONS**

	35-42	43-48	
Carton H x W x D (cm)	33,5 x 41,5 x 61,5	36,5 x 43,5 x 64	
Carton (cbm)	0,0855	0,1016	

TECHNICAL SHEET

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	233	240	247	253	260	267	273	280	287	293	300	307	313	320	-	-	-
Foot length cm	22,8	23,5	24,2	24,8	25,5	26,2	26,8	27,5	28,2	28,8	29,5	30,2	30,8	31,5	-	-	-

**DESCRIPTION**

Safety shoes with microfibre upper with brushed finish for universal use. The toe cap is protected by a TPU protector and the heel is stabilised by a TPU guard. Outsole made of two-component PU provides comfort when worn outdoors or indoors.



**ARDON®**  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2022 Personal protective equipment - Safety footwear

Category: S3S SR FO

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
insulation of the bottom of the shoe against heat		
insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3412/35	8592390352828	13,776	1,3776
G3412/36	8592390352569	13,784	1,3784
G3412/37	8592390352576	14,352	1,4352
G3412/38	8592390352583	14,842	1,4842
G3412/39	8592390352590	14,952	1,4952
G3412/40	8592390352606	15,552	1,5552
G3412/41	8592390352613	15,930	1,5930
G3412/42	8592390352620	16,300	1,6300
G3412/43	8592390352637	16,910	1,6910
G3412/44	8592390352644	17,180	1,7180
G3412/45	8592390352651	17,426	1,7426
G3412/46	8592390352668	17,850	1,7850
G3412/47	8592390352675	18,482	1,8482
G3412/48	8592390352682	18,582	1,8582



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL SHEET